

3mm Vibration Motor - 8mm Type
Shown on 6mm Isometric Grid



Product Data Sheet

Pico Vibe™

3mm Vibration Motor - 8mm Type

Model: 303-102

Ordering Information

The model number 303-102 fully defines the model, variant and additional features of the product. Please quote this number when ordering.

For stocked types, testing and evaluation samples can be ordered directly through our online store.

Datasheet Versions

It is our intention to provide our customers with the best information available to ensure the successful integration between our products and your application. Therefore, our publications will be updated and enhanced as improvements to the data and product updates are introduced.

To obtain the most up-to-date version of this datasheet, please visit our website at:

www.precisionmicrodrives.com

The version number of this datasheet can be found on the bottom left hand corner of any page of the datasheet and is referenced with an ascending R-number (e.g. R002 is newer than R001). Please contact us if you require a copy of the engineering change notice between revisions.


If you have any questions, suggestions or comments regarding this publication or need technical assistance, please contact us via email at:

enquiries@precisionmicrodrives.com or call us on +44 (0) 1932 252 482

Key Features

Body Diameter:	3.2 mm [+/- 0.1]
Body Length:	8.1 mm [+/- 0.2]
Ecc. Weight Radius:	2 mm [+/- 0.1]
Ecc. Weight Length:	2.8 mm [+/- 0.1]
Rated Operating Voltage:	3 V
Rated Vibration Speed:	14,500 rpm [+/- 3,500]
Typical Rated Operating Current:	81 mA
Typical Norm. Amplitude:	0.85 G

Typical Vibration Motor Performance Characteristics



Understanding Precision Microdrives Specification and Production Stages

Precision Microdrives Specification Stages				
Precision Microdrives is run on processes and we guide all customers through sets of predefined specification stages as they move from prototype to production. These are designed to allow the flexibility to iterate designs with the eventual certainty required for production parts.				
Base	Sampling	Pre-Production	Production	EOL
Used for factory downselection Typically 0 units	Used for validating prototypes Typically ~ 10 units	Used for validating initial production Typically ~ 1k units	Used for validating mass production Typically >5k+ units	Used as basis for product replacement 'Base' spec Typically 0 units

Precision Microdrives Capabilities and Competences


Precision Motor Testing and Motor Testing Services
When we started PMD there were no commercial testing machines available, so we built our own. Ever since we've continued to develop new motor testing machines & procedures each year. Fast forward to today and we now have the most extensive testing facilities in the world for sub 40mm diameter motors, gear motors and vibration motors. These are used to validate motors through specification stages and during manufacturing. We also test motors as a service, provide easy to read reports and assist customers with their interpretation.



Motor Customisation, Design, and Manufacturing
To be useful motors need to be integrated with other parts, such as housings or couplings . We routinely develop and produce complete assemblies, from motors with customised leads or connectors to complete electromechanical mechanisms and integrated control electronics. We will support and guide you through the specification stages from prototype to signing-off for mass production.



Competent and Dependable Supply Chains for Production
Most of the worlds miniature motors are made in Asia, and you need engineers on the factory floor who can maintain the Western values of "doing things right" whilst supporting the Asian values of "getting things done". As a customer you are supported by expert eyes, right at the heart of the manufacturing process where it is needed: On the ground in the UK, Hong Kong, and China.



Quality Engineers on the Ground and Local Engineering Teams
The nature of our business is to confidently produce and supply motors 'On time & To spec'. Our customers benefit from our certified ISO 9001 quality systems, reliable motor production infrastructure, and experience. We have a core competence in helping customers design out over-specified and expensive European drives, with more cost-effective, adequately specified, and verified Asian alternatives.



Physical Specification

PARAMETER	CONDITIONS	SPECIFICATION
Body Diameter	Max body diameter or max face dimension where non-circular	3.2 mm [+/- 0.1]
Body Length	Excl. shafts, leads and terminals	8.1 mm [+/- 0.2]
Unit Weight		1 g
No. of Output Shafts		1
Ecc. Weight Radius	Radius from shaft for non-cylindrical weights	2 mm [+/- 0.1]
Ecc. Weight Length		2.8 mm [+/- 0.1]

Construction Specification

PARAMETER	CONDITIONS	SPECIFICATION
Motor Construction		Coreless
Commutation		Precious Metal Brush
No. of Poles		3

Leads & Connectors Specification

PARAMETER	CONDITIONS	SPECIFICATION
Lead Length	Lead lengths defined as total length or between motor and connector	20 mm [+/- 1]
Lead Strip Length		1.5 mm [+/- 0.5]
Lead Configuration		Straight

Operational Specification

PARAMETER	CONDITIONS	SPECIFICATION
Rated Operating Voltage		3 V
Rated Vibration Speed	At rated voltage using the inertial test load	14,500 rpm [+/- 3,500]
Max. Rated Operating Current	At rated voltage using the inertial test load	100 mA
Max. Start Voltage	Certified starting voltage. Measured at no load, where applicable	2 V
Rated Inertial Test Load	Mass of rated load standard test sled	100 g
Max. Operating Voltage		3.6 V
Min. Vibration Amplitude	Peak-to-peak value at rated voltage using the inertial test load	0.5 G
Max. Start Current	At rated voltage	130 mA

Important: The characteristics of the motor is the typical operating parameters of the product. The data herein offers design guidance information only and supplied batches are validated for conformity against the specifications on the previous page.

Typical Performance Characteristics

PARAMETER	CONDITIONS	SPECIFICATION
Typical Rated Operating Current	At rated voltage using the inertial test load	81 mA
Typical Vibration Amplitude	Peak-to-peak value at rated voltage using the inertial test load	0.85 G
Typical Start Current	At rated voltage	113 mA
Typical Vibration Efficiency	At rated voltage using the inertial test load	3.6 G/W
Typical Norm. Amplitude	Peak-to-peak vibration amplitude normalised by the inertial test load at rated voltage	0.85 G
Typical Start Voltage	Measured at no load, where applicable	1.1 V
Typical Terminal Resistance		30 Ohm
Typical Terminal Inductance		65 uH


Typical Haptic Characteristics

PARAMETER	CONDITIONS	SPECIFICATION
Typical Lag Time	At rated voltage using the inertial test load	26 ms
Typical Rise Time	At rated voltage using the inertial test load	44.5 ms
Typical Stop Time	At rated voltage using the inertial test load	45.5 ms
Typical Active Brake Time	Time taken from steady-state to 0.04 G under inverse polarity at max. voltage	22 ms

Environmental Characteristics

PARAMETER	CONDITIONS	SPECIFICATION
Max. Operating Temp.		70 Deg.C
Min. Operating Temp.		-30 Deg.C
Max. Storage & Transportation Temp.		80 Deg.C
Min. Storage & Transportation Temp.		-40 Deg.C

Product Dimensional Specification



Life Support Policy

PRECISION MICRODRIVES PRODUCTS ARE NOT AUTHORISED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF PRECISION MICRODRIVES LIMITED.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



Tel:
 Fax:
 Email:
 Web:

VAT Registration.